

# PRATIKA 55 SMART PLUS

#### **AUTOMATIC PACKAGING MACHINE - L-SEALING - INTEGRATED TUNNEL**



### **DESCRIPTION**

The new version of the shrink wrap machine **Pratika 55 Smart Plus** comes from a constant attention to the needs of the market, with the aim of proposing a technologically advanced product, but flexible and extremely compact. The included tunnel, revolutionary in the world of automatic machines, meets the space requirements, but above all reduces labour costs to a minimum, thanks to the patented option "come back" to a single operator.

Enhanced with strong technological, mechanical and electronic contents, the new **Pratika 55 Smart Plus** represents a perfect synthesis of reliability, versatility and safety, by which the way of conceiving the shrink wrap machine with compact automatic operation evolves one more time.

#### **TECHNICAL FEATURES**



Power supply	220V 50/60Hz 3Ph 400V 3Ph + N
Max installed power (including tunnel)	8,5 kW (220 V) 9 kW (400 V)
Maximum current	22 A (220V) 15 A (400V)
Hourly production	0-1200 p/h
Max product dimensions	400x420x120 mm
Max reel dimensions (Ø x length)	Ø250x600 mm
Worktop height	870 mm (infeed belt h.)
Machine dimensions (guards closed)	2445x1160x1625 mm
Machine dimensions (guards open)	2445x2175x1625 mm
Usable film	Polyolefin 9-38 micron
Machine weight	710 / 845 kg

minipack®-torre shall not be held liable for typos or printing errors in this catalogue. It also reserves the right to make changes to the specified features without prior notice. All trademarks are property of their respective owners and are hereby acknowledged.

## **TECHNICAL DRAWING**





