



D541 Continuous Sealer

→ *The new compact machine that's big on performance*

 AUDION

Packaging machines

D541 CONTINUOUS SEALER

The new compact machine that's big on performance

Introducing a new standard in versatility, the Audion D541 is a compact stand-alone continuous sealer that's ideal for a multitude of applications. Its unique new ergonomic design, light weight and touch button operation provide outstanding mobility, while fast-heating ceramic elements and flexible positioning mean it's always convenient to use.

Easy to operate and with an excellent quality-price ratio, the Audion D541 is the perfect machine for small businesses, social enterprises and any department that needs a fast, flexible sealing solution.

Portable and adjustable

Weighing in at under 6kg, the Audion D541 is the lightest machine on the market and, thanks to its ergonomic grip, it can easily be carried while walking to seal long lanes of film. Non-fading touch buttons allow no-fuss on-the-go operation.

Positioning the Audion D541 is never a problem as it can be used both horizontally and vertically, so pre-made bags can be sealed either hanging or lying flat. A vertical support makes it easy to tilt the machine, adjust its height or even mount on a wall. An optional work table can be used to steady the positioning of bags as they are being sealed to prevent contents from spilling.



Fast and flexible

Thanks to ceramic heating elements that are ready to use in less than 1 minute, the Audion 541 is ready to work fast. Its automatic cool-down feature preserves energy and safety. An adjustable in-feed guide ensures correct positioning of the seal as required by different packages.

Wide range of applications

With its quality performance, versatile capabilities, ease of use and low price-point, the Audion 541 is ideal for use in a wide range of sectors. It's suitable for small runs, continuous packaging (long seals) and much more. The use of PTFE-belts means that Polyethylene, Polypropylene, Cellophane and thin laminates can all be sealed.

Accessories



work table



wall mount



vertical stand



Technical specifications	D541
Infeed adjustable in height (from top of seal to top of package)	± 9-36 mm
Sealing width	4 mm
Conveyor speed	5 mtr/min
Temperature digitally adjustable	up to 200 °C
Max. packaging weight vertical (unsupported)	150 gr.
Film thickness (PE film)	min. 2 x 20 / max. 2 x 120 micron
Machine weight	5,7 kg
Machine dimensions (WxDxH)	386 x 232 x 90 mm
Voltage	230 V - 1 ph- 50/60 Hz
Power consumption	400 W