

| Technical details               | D662 MCV                              | D666 MPCV        | D775 MPCV                            |
|---------------------------------|---------------------------------------|------------------|--------------------------------------|
| Dimensions                      | 473 x 235 x 181 mm                    | 554 x 270 x 222  | 621 x 300 x 330 mm                   |
| Weight                          | 12,5 kg                               | 18,5 kg          | 26 kg                                |
| Consumption                     | 500 W                                 | 600 W            | 600 W                                |
| Power supply                    | 230 V                                 | 230 V            | 230 V                                |
| Seal speed                      | 6 m/min                               | 10 m/min         | 13 m/min                             |
| Seal width                      | 12,5/12,5 mm multi-line mm multi-line | 15 mm multi-line | 15 mm multi-line                     |
| Temperature range               | 10 - 200 C                            | Max. 200 C       | Max. 200 C                           |
| Temperature controller accuracy | +/- 1%                                | +/- 1%           | +/- 1%                               |
| Temperature alarm limits        | - 5 °C / + 5 °C                       | - 5 °C / + 5 °C  | - 5 °C / + 5 °C                      |
| Pressure alarm limits           | - 15 N / + 17 N                       | +/- 20N          | +25N or -15N                         |
| Speed alarm limits              | - 0,5 mm/min. / + 1,0 m/min.          | +5% or -7%       | ± 0,5 m/min.                         |
| Display                         | LCD 2 lines                           | LCD 4 lines      | LCD 2 lines                          |
| Connection port                 | 1x USB port                           | 1x USB port      | External LAN connection traceability |