

Technical details	D660 V	D662 MCV	D666 MPCV	D775 MPCV
Dimensions	590 x 270 x 2380mm	473 x 235 x 181 mm	554 x 270 x 222	621 x 300 x 330 mm
Weight	18,0 kg	12,5 kg	18,5 kg	26 kg
Consumption	500 W	500 W	600 W	600 W
Power supply	230 V	230 V	230 V	230 V
Seal speed	6 m/min	6 m/min	10 m/min	13 m/min
Seal width	9 mm cross hatch	12,5/12,5 mm multi-line mm multi-line	15 mm multi-line	15 mm multi-line
Temperature range	110 - 220 C	10 - 200 C	Max. 200 C	Max. 200 C
Temperature controller accuracy	+/- 1%	+/- 1%	+/- 1%	+/- 1%
Temperature alarm limits	- 5 °C / + 5 °C	- 5 °C / + 5 °C	- 5 °C / + 5 °C	- 5 °C / + 5 °C
Pressure alarm limits	-	- 15 N / + 17 N	+/- 20N	+25N or -15N
Speed alarm limits	-	- 0,5 mm/min. / + 1,0 mm/min.	+5% or -7%	± 0,5 mm/min.
Display	LCD 2 lines LCD 2 lines	LCD 2 lines	LCD 4 lines	LCD 2 lines
Connection port	1x USB port	1x USB port	1x USB port	External LAN connection traceability