

| Technical details              | VAL VAC PSR 520    | VAL VAC PSR 720    | VAL VAC PSR 1020    |
|--------------------------------|--------------------|--------------------|---------------------|
| Seal length                    | 520 mm             | 720 mm             | 1020 mm             |
| Seal width                     | 8 mm               | 8 mm               | 8 mm                |
| Stainless steel                | x                  | x                  | x                   |
| Gas flush                      | x                  | x                  | x                   |
| Bi-active sealing bars         | x                  | x                  | x                   |
| Multi cycle                    | x                  | x                  | x                   |
| Digital panel                  | x                  | x                  | x                   |
| Dimensions                     | 590 x 232 x 487 mm | 790 x 232 x 487 mm | 1110 x 232 x 487 mm |
| Venturi pump                   | 11,3 m3/time       | 11,3 m3/time       | 11,3 m3/time        |
| Foot pedal                     | x                  | x                  | x                   |
| Validation version             | x                  | x                  | x                   |
| Digital temperature controller | x                  | x                  | x                   |
| RS 232 connection              | x                  | x                  | x                   |
| Film thickness                 | 40 - 400 my        | 40 - 400 my        | 40 - 400 my         |
| Voltage                        | 230 V              | 230 V              | 230 V               |
| Consumption                    | 2500 W             | 3000 W             | 2600 W              |
| Air pressure                   | > 6 bar            | > 6 bar            | > 6 bar             |
| IP value                       | IP 20              | IP 20              | IP 20               |